# Getac



# VR-X20 DVR G3

VR-X20 DVR G3 features Al-empowered computing platform that supports ALPR, merges video and data from multiple sources at once, and enables multi-tasking.



## Al PC Performance for Multi-Tasking

Feature with the Intel® Core™ Ultra 5 processor 125H, delivering faster speed and improved power-saving capability for AI applications.



## Military-Grade Durability

MIL-STD-810H compliant. Built to withstand extreme environments, ensuring consistent performance in a wide temperature range from -22°F to 158°F.



## **Multiple Connectivity Options**

Offer dual LAN, Wi-Fi 7, GPS, and Bluetooth with faster data streaming speed. GPS supports L1 and L5.



## **Long-Term Reliability**

A 3-year warranty ensures continued service support and device longevity. An extended warranty is also available with additional purchase.



## **Backup Battery**

Powerful backup battery keeps you fully functional in case of vehicle collision or dead battery.

## **Specifications**

Operating System
Windows 11 IoT Enterprise

Intel® Core™ Ultra 5 Processor 125H Max. 4.5GHz with Intel® Turbo Boost Technology - 18MB Intel® Smart Cache

#### **Memory & Storage**

#### 8GB DDR5

Optional: 16GB / 32GB DDR5

1st storage: 256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCle NVMe SSD

2<sup>nd</sup> storage: 256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

#### **GPU**

Intel® Arc™ Graphics

#### NPU

Intel® Al Boost

#### I/O Interface

PoE (Power Over Ethernet, PSE) x 6 LAN (RJ45, 2.5Gbps) x 1 LAN (RJ45, 1Gbps) x 1 Audio Jacks (RJ45) x 2 Serial port (9-pin; D-sub) x1 Audio in/out combo x 1 DC in Jack (Power & Ignition) x 1 DC in Jack (Power & Ignition) x 1 USB 2.0 Type-A x 1 USB 3.1 Gen 2 Type-A x 2 USB 4 Gen2x2 Type-C x 1 GPIO Ports (Input x 8, Output x 4, 12V/1A power output x 2) GPS SMA x 1 Wi-Fi MiMo RP-SMA x 2 Control unit connector x 1

#### **Communications**

10/100/1000 BASE-T Ethernet 2.5GBASE-T Ethernet Intel® Wi-Fi 7 BE202, 802.11be Bluetooth (v5.4)

#### Security

TPM 2.0

#### **Power**

Li-Ion battery (7.26V, typical 9600mAh; min. 9400mAh)

#### Ruggedness

MIL-STD-810H compliant

#### **Temperature**

Operating: -30°C to 70°C / -22°F to 158°F Storage: -40°C to 85°C / -40°F to 185°F

Dimensions (W x D x H) & Weight 182 x 68.5 x 179mm (7.16" x 2.69" x 7.04") 2.08kg (4.59lbs)

#### Warranty

3-year standard limited warranty

- \* Extended plans available.
- \* Specification subject to change. Custom options are available based on customer specifications.

# **VR-X20**



## Getac

#### **Getac USA**

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel: 949-681-2900 GetacSales\_US@getac.com | www.getac.com/us/

Copyright © 2025 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V01M03Y25U5

